

JavaMaster 1500 Roaster Specification

Roaster Footprint

- 246 lbs.
- 17" w x 70" h x 25" d
- High performance medical grade swivel casters, 4" diameter

Materials and Finishes

- Heavy Duty Steel Powder Coated for anti-corrosion (black and red standard, custom colors upon request)
- Lighted 7"x18", Roaster chamber made of thermal shock resistant borosilicate glass, removable for easy cleaning

Capacity

- Model 1500 and 1500E: 1 to 4 lbs. per batch, yielding 16 lbs. per hour
- 5-to-10-minute roast time, 4-to-5-minute cool down

Connectivity

- Touchpad enabled
- Data Download available

Warranty

- Lifetime craftsmanship (with proper usage)
- 3 Year temperature controllers
- All other 1-year parts & labor

Facilities Requirements

- 208/120V Single-phase
- 60A service (55A peak)
- 1/4" water line, filtered for roast quench
- ETL Listed – UL197 Canada certified CSA STD C22.2, No109
- Exhaust ventilation required – 410 CFM upblast blower min
- No gas supply nor drain required

1500E Enhanced Package

- 300 Roast Profiles included
- Custom profiles can be defined and programmed
- Ready2Roast chamber pre-warm-up
- Barcode scanner for profile selection
- Roast performance graphing and statistics
- Wireless Connectivity